

TITLE OF THE INVENTION
IMAGE SEARCH APPARATUS AND METHOD, AND COMPUTER READABLE
MEMORY

5 BACKGROUND OF THE INVENTION

6 The present invention relates to an image search
apparatus and method for searching an image database
that stores a plurality of image data for desired image
10 data, and a computer readable memory.

Various image search apparatuses for searching
databases which store a large number of image data for
desired image data have been proposed. The search
methods used in these image search apparatuses are
15 roughly classified into two methods:

- a method of storing non-image information such as
keywords, photographing dates, and the like in
association with image data, and conducting a search
based on such information; and
- 20 · a method of conducting a search on the basis of
the image feature amounts (luminance/color difference
information, image frequency, histogram, and the like)
of image data itself.

In the latter method, a method of submitting
25 certain image data, and searching image data using the
image feature amounts of that image data as query keys

is called similar image search. This method can effectively provide a search interface which is friendly to a user who has no special knowledge about image processing.

5 However, when a handwritten illustration is used as a query criteria in a similar image search, a desired image cannot be obtained unless an appropriate illustration is drawn, thus requiring drawing skills or troublesome works in drawing. Also, a desired image
10 cannot be obtained unless colors used in drawing are appropriate. Furthermore, the color to be used is normally designated on the basis of numerical values such as R, G, and B luminance values, or the like. However, it is not easy for the user who has no
15 knowledge about the image processing to immediately understood such values, thus disabling efficient search operation.

SUMMARY OF THE INVENTION

20 The present invention has been made in consideration of the aforementioned problems, and has as its object to provide an image search apparatus and method, which can quickly reflect user's will, and can efficiently make an image search, and a computer
25 readable memory.

In order to achieve the above object, an image search apparatus according to the present invention comprises the following arrangement.

That is, an image search apparatus for searching
5 an image database that stores a plurality of image data for desired image data, comprises:

storage means for storing the plurality of image data in correspondence with image feature amounts of the image data;

10 input means for inputting an image using an input window;

image feature amount computing means for computing an image feature amount of the image input by the input means;

15 image similarity computing means for computing image similarity on the basis of the image feature amount computed by the image feature amount computing means, and the image feature amounts of the image data stored in the storage means;

20 image display means for displaying a list of image data as search results on the basis of the image similarity computed by the image similarity computing means; and

read-out means for reading out the image data
25 stored in the storage means into the input window.

In order to achieve the above object, an image search method according to the present invention comprises the following arrangement.

That is, an image search method for searching an
5 image database that stores a plurality of image data for desired image data, comprises:

the storage step of storing the plurality of image data in a storage medium in correspondence with image feature amounts of the image data;

10 the image feature amount computing step of computing an image feature amount of an image input on an input window;

the image similarity computing step of computing image similarity on the basis of the image feature
15 amount computed in the image feature amount computing step, and the image feature amounts of the image data stored in the storage medium in the storage step;

the image display step of displaying a list of image data as search results on the basis of the image
20 similarity computed in the image similarity computing step; and

the read-out step of reading out the image data stored in the storage step into the input window.

In order to achieve the above object, a computer
25 readable memory according to the present invention comprises the following arrangement.

That is, a computer readable memory that stores a program code of an image search for searching an image database that stores a plurality of image data for desired image data, comprises:

5 a program code of the storage step of storing the plurality of image data in a storage medium in correspondence with image feature amounts of the image data;

 a program code of the image feature amount
10 computing step of computing an image feature amount of an image input on an input window;

 a program code of the image similarity computing
step of computing image similarity on the basis of the
image feature amount computed in the image feature
15 amount computing step, and the image feature amounts of
the image data stored in the storage medium in the
storage step;

 a program code of the image display step of
displaying a list of image data as search results on the
20 basis of the image similarity computed in the image
similarity computing step; and

 a program code of the read-out step of reading out
the image data stored in the storage step into the input
window.

In order to achieve the above object, an image search apparatus according to the present invention comprises the following arrangement.

That is, an image search apparatus for searching
5 an image database that stores a plurality of image data for desired image data, comprises:

storage means for storing the plurality of image data in correspondence with image feature amounts of the image data;

10 input means for inputting an image using an input window;

image feature amount computing means for computing an image feature amount of the image input by the input means;

15 image similarity computing means for computing image similarity on the basis of the image feature amount computed by the image feature amount computing means, and the image feature amounts of the image data stored in the storage means;

20 image display means for displaying a list of image data as search results on the basis of the image similarity computed by the image similarity computing means; and

designation means for designating a color used in
25 the image to be drawn by the input means on the basis of the image data displayed by the image display means.

In order to achieve the above object, an image search method according to the present invention comprises the following arrangement.

That is, an image search method for searching an
5 image database that stores a plurality of image data for desired image data, comprises:

the storage step of storing the plurality of image data in a storage medium in correspondence with image feature amounts of the image data;

10 the image feature amount computing step of computing an image feature amount of an image input on an input window;

the image similarity computing step of computing image similarity on the basis of the image feature
15 amount computed in the image feature amount computing step, and the image feature amounts of the image data stored in the storage medium in the storage step;

the image display step of displaying a list of image data as search results on the basis of the image
20 similarity computed in the image similarity computing step; and

the designation step of designating a color used in the image to be drawn on the input window on the basis of the image data displayed in the image display
25 step.

In order to achieve the above object, a computer readable memory according to the present invention comprises the following arrangement.

That is, a computer readable memory that stores a
5 program code of an image search for searching an image database that stores a plurality of image data for desired image data, comprises:

a program code of the storage step of storing the plurality of image data in a storage medium in
10 correspondence with image feature amounts of the image data;

a program code of the image feature amount computing step of computing an image feature amount of an image input on an input window;

15 a program code of the image similarity computing step of computing image similarity on the basis of the image feature amount computed in the image feature amount computing step, and the image feature amounts of the image data stored in the storage medium in the
20 storage step;

a program code of the image display step of displaying a list of image data as search results on the basis of the image similarity computed in the image similarity computing step; and

25 a program code of the designation step of designating a color used in the image to be drawn on the

input window on the basis of the image data displayed in the image display step.

In order to achieve the above object, an image search apparatus according to the present invention
5 comprises the following arrangement.

That is, an image search apparatus for searching an image database that stores a plurality of image data for desired image data, comprises:

storage means for storing the plurality of image
10 data in correspondence with image feature amounts of the image data;

selection means for selecting one of a plurality of different input methods;

input means for inputting an image using the input
15 method selected by the selection means;

image feature amount computing means for computing an image feature amount of the image input by the input means;

image similarity computing means for computing
20 image similarity on the basis of the image feature amount computed by the image feature amount computing means, and the image feature amounts of the image data stored in the storage means; and

image display means for displaying a list of image
25 data as search results on the basis of the image

similarity computed by the image similarity computing means.

In order to achieve the above object, an image search method according to the present invention
5 comprises the following arrangement.

That is, an image search method for searching an image database that stores a plurality of image data for desired image data, comprises:

the storage step of storing the plurality of image
10 data in a storage medium in correspondence with image feature amounts of the image data;

the selection step of selecting one of a plurality of different input methods;

the input step of inputting an image using the
15 input method selected in the selection step;

the image feature amount computing step of computing an image feature amount of an image input in the input step;

the image similarity computing step of computing
20 image similarity on the basis of the image feature amount computed in the image feature amount computing step, and the image feature amounts of the image data stored in the storage medium in the storage step; and

the image display step of displaying a list of
25 image data as search results on the basis of the image

similarity computed in the image similarity computing step.

In order to achieve the above object, a computer readable memory according to the present invention
5 comprises the following arrangement.

That is, a computer readable memory that stores a program code of an image search for searching an image database that stores a plurality of image data for desired image data, comprises:

10 a program code of the storage step of storing the plurality of image data in a storage medium in correspondence with image feature amounts of the image data;

a program code of the selection step of selecting
15 one of a plurality of different input methods;

a program code of the input step of inputting an image using the input method selected in the selection step;

a program code of the image feature amount
20 computing step of computing an image feature amount of an image input in the input step;

a program code of the image similarity computing step of computing image similarity on the basis of the image feature amount computed in the image feature
25 amount computing step, and the image feature amounts of

the image data stored in the storage medium in the storage step; and

a program code of the image display step of displaying a list of image data as search results on the basis of the image similarity computed in the image
5 similarity computing step.

Other features and advantages of the present invention will be apparent from the following description taken in conjunction with the accompanying drawings, in
10 which like reference characters designate the same or similar parts throughout the figures thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the arrangement
15 of an image search apparatus according to the first embodiment of the present invention;

Fig. 2 shows a control window displayed on a display unit upon executing a search process of the first embodiment;

20 Fig. 3 is a flow chart showing an outline of the processes executed by the image search apparatus of the first embodiment;

Fig. 4 is a flow chart showing the details of the process executed in step S191 in the first embodiment;

Fig. 5 is a view for explaining image segmentation for extracting an image feature amount in the first embodiment;

Fig. 6 is a flow chart showing the computation process of the image feature amount in the first embodiment;

Fig. 7 is a flow chart showing the details of the method of computing the R, G, and B average values in the first embodiment;

Fig. 8 is a flow chart showing the computation process of an image distance $S(n)$ in the first embodiment;

Fig. 9 is a flow chart showing the details of the similar image search process in the first embodiment;

and

Fig. 10 is a flow chart showing an outline of the processes executed by an image search apparatus of the second embodiment.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The preferred embodiments of the present invention will be described in detail hereinafter with reference to the accompanying drawings.

<First Embodiment>

Fig. 1 is a block diagram showing the arrangement of an image search apparatus according to the first embodiment.

Referring to Fig. 1, reference numeral 101 denotes
5 a CPU for controlling the entire system. Reference numeral 102 denotes a keyboard; and 102a, a pointing device (mouse). The keyboard 102 is used together with the mouse for inputting data into the system and drawing an illustration which is used as a query criteria for a
10 similar image search. Reference numeral 103 denotes a display unit which comprises a CRT, liquid crystal display, or the like, and displays a user interface used for drawing an image serving as a query criteria, and image data as a search result, and the like. Reference
15 numeral 104 denotes a ROM; and 105, a RAM. These ROM and RAM construct a memory device of the system, and store programs executed by the system and data used by the system. Reference numeral 106 denotes a hard disk device; and 107, a floppy disk device. The hard disk
20 device and floppy disk device construct an external storage device used as a file system of the system. The hard disk device 106 stores a plurality of image data to be searched. Reference numeral 108 denotes a printer for recording an image or the like displayed on the display
25 unit 103 on a recording medium.

The control window displayed on the display unit 103 upon executing the search process of the first embodiment will be explained below with reference to Fig. 2.

5 Fig. 2 shows the control window displayed on the display unit upon executing the search process in the first embodiment.

Reference numeral 21 denotes a user drawing area; 22, a cursor; 23, color selection scroll bars; 24, a
10 clear button; 25, a search button; 27, a next candidate display button; and 28, a processing end button. Also, reference numerals 26a to 26h denote areas for displaying icon images corresponding to image data as search results. Reference numeral 29 denotes a random
15 button.

The user can draw an illustration, which is similar to the image wanted and used as a query criteria, on the user drawing area 21 using the drawing tools implemented by software. The software process upon
20 drawing an illustration will be briefly described below.

The color selection scroll bars 23 are used for selecting a pen color used in drawing, and designate R, G, and B values in turn from the uppermost one. Upon pressing the clear button 24, the entire user drawing
25 area 21 is painted in white. The user moves the cursor 22 using the pointing device 102a and can draw a free

curve on the user drawing area 21. Upon pressing the processing end button 28, the control window is closed, and the processing ends. Upon pressing the random button 29, image data stored in the hard disk device 106 are
5 randomly selected, and icon images corresponding to the selected image data are displayed on the areas 26a to 26h.

An outline of the processes executed by the image search apparatus of the first embodiment will be
10 explained below with reference to Fig. 3.

Fig. 3 is a flow chart showing an outline of the processes executed by the image search apparatus of the first embodiment.

In step S191, the user draws an illustration,
15 which is similar to the image data wanted and stored on the hard disk device 106, and is used as a query criteria, on the display unit 103. In step S192, the image feature amount of the drawn illustration is computed. In step S193, a similar image search is made
20 on the basis of the computed image feature amount. In step S194, similar images (icon images) found by search are displayed on the display unit 103. It is then checked in step S195 if the user has clicked a given displayed icon image using the pointing device 102a. If
25 the user has clicked the icon image (YES in step S195), the flow advances to step S196. On the other hand, if

the user has not clicked any icon image (NO in step S195), the flow advances to step S197.

In step S196, the icon image selected in step S195 is copied onto the user drawing area 21, and the flow
5 returns to step S192.

It is checked in step S197 if search operation is to end. If search operation is not to end (NO in step S197), the flow returns to step S191. On the other hand, if search operation is to end (YES in step S197), the
10 processing ends.

With the above-mentioned processes, if the list of icon images displayed as the search results contains an image which is close to a desired image, the user need only click that icon image, and the selected icon image
15 is copied onto the user drawing area 21. The user can modify the copied image to generate a new illustration (image) used as a query criteria, and can make a similar image search again. At the instance of clicking that illustration (image), a similar image search is
20 automatically started using the illustration (image) as a query criteria.

The details of the processes executed in the individual steps will be described below.

{Description of Step S191}

25 In step S191, the user draws an illustration, which is used as a query criteria, on the user drawing

area 21, and the flow advances to the next step S192 at an appropriate timing. The process at that time will be explained below with reference to Fig. 4. At that timing, the system monitors the movement of the mouse 102a, and every time a movement is monitored, the image feature amount of the image drawn so far is computed.

Fig. 4 is a flow chart showing the details of the process executed in step S191 in the first embodiment.

Note that x0 and y0 are variables for storing the previous position of the cursor 22, and x1 and y1 are variables that store the current position of the cursor 22.

It is checked in step S31 if the user has moved the mouse 102a. If the user has not moved the mouse yet (NO in step S31), the flow returns to step S31. That is, the process in this step forms a loop for monitoring the movement of the mouse 102a. On the other hand, if the user has moved the mouse (YES in step S31), the flow advances to step S32.

It is checked in step S32 if the mouse button of the mouse 102a is being held down. If the mouse button is not held down (NO in step S32), the flow advances to step S34 to substitute the current position (x1, y1) of the cursor 22 in (x0, y0), and the flow returns to step S31. In this manner, the cursor 22 alone can be moved without drawing any stroke.

On the other hand, if the mouse button is being held down (YES in step S32), i.e., if the user is dragging the mouse, the flow advances to step S33. In step S33, a line is drawn between the previous position (x0, y0) and the current position (x1, y1) of the cursor in a color determined by the color selection scroll bars 23.

In step S35, the current position (x1, y1) of the cursor 22 is substituted in (x0, y0) to end step S191, and the flow advances to step S192.

This process makes the user feel as if a search were automatically executed every time he or she adds a stroke to the illustration.

{Description of Step S192}

In step S192, the image feature amount of the illustration drawn in step S191 is computed.

As shown in Fig. 5, the size of the user drawing area 21 in the first embodiment is defined by W pixels (horizontal) \times H pixels (vertical). This area is segmented into a total of six sub-areas, i.e., 3 (horizontal) \times 2 (vertical) sub-areas (0, 0), (1, 0), ..., (2, 1) in turn from the upper left sub-area. The R, G, and B average values of these sub-areas are computed, and a total of 18 numerical values are used as the image feature amount of the drawn illustration.

The computation process of the image feature amount will be described below with reference to Fig. 6.

Fig. 6 is a flow chart showing the computation process of the image feature amount in the first
5 embodiment.

In step S51, a variable k is initialized to zero. In step S52, a variable j is initialized to zero. In step S53, a variable i is initialized to zero. In step S54, the R average value of a sub-area (i, j) is
10 substituted in the k-th element d(k) of a matrix d. Also, the G and B average values are respectively substituted in d(k+1) and d(k+2). Note that the method of computing the R, G, and B average values will be described in detail later with the aid of the flow chart in Fig. 7.

15 In step S55, k is incremented by "3". In step S56, i is incremented by "1". In step S57, i is compared with "2". If $i > 2$ (YES in step S57), the flow advances to step S58. On the other hand, if $i \leq 2$ (NO in step S57), the flow returns to step S54.

20 In step S58, the variable j is incremented by "1". In step S59, the variable j is compared with "1". If $j > 1$ (YES in step S59), the process ends. On the other hand, if $j \leq 1$ (NO in step S59), the flow returns to step S53.

Upon completion of the process, the computed
25 values of the image feature amount of the drawn illustration are stored in the matrix d() having 18

elements. Note that the drawn illustration (image) is segmented into six rectangular areas having equal areas to compute image feature amount values in this embodiment. However, the shape of the segmented area is not limited to a rectangle but may be other complicated shapes, and the number of segmented areas may be increased/decreased. When the number of segmented areas is increased/decreased, the number of elements of the image feature amount is not 18 but increases/decreases accordingly.

The method of computing the R, G, and B average values in step S54 in Fig. 6 will be described in detail below using Fig. 7.

Fig. 7 is a flow chart showing the details of the method of computing the R, G, and B average values in the first embodiment.

Assume that image data of the drawn illustration is stored in three matrices $R(X, Y)$, $G(X, Y)$, and $B(X, Y)$. Note that $0 \leq X < W$ and $0 \leq Y < H$, and the start point $(0, 0)$ is set at the upper left corner of the image. In the following flow, the R, G, and B average values of an area within the range of $X_0 \leq X < X_1$ and $Y_0 \leq Y < Y_1$ are calculated, and are respectively returned to variables DR, DG, and DB. Furthermore, since an area corresponding to the sub-area (i, j) in step S192 corresponds to:

$$X0 = W*i/3 \quad X1 = W*(i + 1)/3$$

$$Y0 = H*j/2 \quad Y1 = H*(j + 1)/2$$

the flow chart is executed after constants X0, X1, Y0, and Y1 are initialized, as described above.

5 In step S61, the variables DR, DG, and DB are initialized to zero. In step S62, a variable Y is initialized to Y0. In step S63, a variable X is initialized to X0. In step S64, R(X, Y) is added to the variable DR. Similarly, G(X, Y) and B(X, Y) are
10 respectively added to the variables DG and DB.

 In step S65, the variable X is incremented by "1". In step S66, the variable X is compared with X1. If X = X1 (YES in step S66), the flow advances to step S67. On the other hand, if X \neq X1 (NO in step S66), the flow
15 returns to step S64.

 In step S67, the variable Y is incremented by "1". In step S68, the variable Y is compared with Y1. If Y = Y1 (YES in step S68), the flow advances to step S69. On the other hand, if Y \neq Y1 (NO in step S68), the flow
20 returns to step S63. In step S69, the variables DR, DG, and DB are respectively divided by (X1 - X0)*(Y1 - Y0). This divisor indicates the number of pixels in the area. That is, the variables DR, DG, and DB indicate the average densities obtained by dividing the sum totals of
25 pixel densities in the area by the number of pixels.

{Description of Step S193}

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100																																																																																																																																																											
0	00000000	00000001	00000010	00000011	00000100	00000101	00000110	00000111	00001000	00001001	00001010	00001011	00001100	00001101	00001110	00001111	00010000	00010001	00010010	00010011	00010100	00010101	00010110	00010111	00011000	00011001	00011010	00011011	00011100	00011101	00011110	00011111	00100000	00100001	00100010	00100011	00100100	00100101	00100110	00100111	00101000	00101001	00101010	00101011	00101100	00101101	00101110	00101111	00110000	00110001	00110010	00110011	00110100	00110101	00110110	00110111	00111000	00111001	00111010	00111011	00111100	00111101	00111110	00111111	01000000	01000001	01000010	01000011	01000100	01000101	01000110	01000111	01001000	01001001	01001010	01001011	01001100	01001101	01001110	01001111	01010000	01010001	01010010	01010011	01010100	01010101	01010110	01010111	01011000	01011001	01011010	01011011	01011100	01011101	01011110	01011111	01100000	01100001	01100010	01100011	01100100	01100101	01100110	01100111	01101000	01101001	01101010	01101011	01101100	01101101	01101110	01101111	01110000	01110001	01110010	01110011	01110100	01110101	01110110	01110111	01111000	01111001	01111010	01111011	01111100	01111101	01111110	01111111	10000000	10000001	10000010	10000011	10000100	10000101	10000110	10000111	10001000	10001001	10001010	10001011	10001100	10001101	10001110	10001111	10010000	10010001	10010010	10010011	10010100	10010101	10010110	10010111	10011000	10011001	10011010	10011011	10011100	10011101	10011110	10011111	10100000	10100001	10100010	10100011	10100100	10100101	10100110	10100111	10101000	10101001	10101010	10101011	10101100	10101101	10101110	10101111	10110000	10110001	10110010	10110011	10110100	10110101	10110110	10110111	10111000	10111001	10111010	10111011	10111100	10111101	10111110	10111111	11000000	11000001	11000010	11000011	11000100	11000101	11000110	11000111	11001000	11001001	11001010	11001011	11001100	11001101	11001110	11001111	11010000	11010001	11010010	11010011	11010100	11010101	11010110	11010111	11011000	11011001	11011010	11011011	11011100	11011101	11011110	11011111	11100000	11100001	11100010	11100011	11100100	11100101	11100110	11100111	11101000	11101001	11101010	11101011	11101100	11101101	11101110	11101111	11110000	11110001	11110010	11110011	11110100	11110101	11110110	11110111	11111000	11111001	11111010	11111011	11111100	11111101	11111110	11111111

T0240

$$S(n) = \sum_i (D(n, i) - d(i))^2$$

- 23 -

process for selecting M image data will be respectively described below using Figs. 8 and 9.

Fig. 8 is a flow chart showing the computation process of the image distance $S(n)$ in the first
5 embodiment.

In step S71, variables min and n are initialized to zero, and a variable L is initialized to a sufficiently large value. In step S72, variables i and $S(n)$ are initialized to zero. In step S73, a square of
10 the difference between $D(n, i)$ and $d(i)$ is added to $S(n)$. In step S74, the variable i is incremented by "1".

In step S75, the variable i is compared with "18". If $i = 18$ (YES in step S75), the flow advances to step S76. On the other hand, if $i \neq 18$ (NO in step S75), the
15 flow returns to step S73.

In step S76, the variable n is incremented by "1". In step S77, the variable n is compared with N. If $n = N$ (YES in step S77), the processing ends. On the other hand, if $n \neq N$ (NO in step S77), the flow returns to
20 step S72.

Upon completion of the process, the image distances $S(n)$ between the drawn illustration (image data) and all the image data stored in the hard disk device 106 are stored in a matrix $S(n)$. A similar image
25 search process for selecting M image data in ascending order of image distance $S(n)$ and storing numbers

corresponding to the selected image order in a matrix
T() will be described in detail below using Fig. 9.

Fig. 9 is a flow chart showing the details of the
similar image search process in the first embodiment.

5 In step S81, a variable j is initialized to zero.
In step S82, a variable i is initialized to zero. In
step S83, a variable min is initialized to zero and a
variable L is initialized to a sufficiently large value.
In step S84, S(i) is compared with L. If S(i) < L (YES
10 in step S84), the flow advances to step S85. On the
other hand, if S(i) ≥ L (NO in step S84), the flow
advances to step S86.

In step S85, the value i is substituted in the
variable min, and S(i) is substituted in L. In step S86,
15 the variable i is incremented by "1". In step S87, i is
compared with N. If i = N (YES in step S87), the flow
advances to step S88. On the other hand, if i ≠ N (NO in
step S87), the flow returns to step S84.

In step S88, the value min is substituted in T(j).
20 In step S89, a sufficiently large value is substituted
in S(min). In step S810, the variable j is incremented
by "1". In step S811, the variable j is compared with M.
If j = M (YES in step S811), the processing ends. On the
other hand, if j ≠ M (NO in step S811), the flow returns
25 to step S82.

Upon completion of the process, the image numbers of image data stored in the hard disk device 106 are stored in the matrix $T(j)$ (for $0 \leq j < M$) in descending order of similarity with the drawn illustration (image data).

{Description of Step S194}

The processing contents will be explained below with reference to the control window shown in Fig. 2.

The areas 26a to 26h respectively display icon images obtained by displaying similar images found by the search process in a reduced scale. The area 26a displays an image corresponding to $T(0)$ with highest similarity, the area 26b displays an image corresponding to $T(1), \dots$, and the area 26h displays an image with lowest similarity among these images.

Note that the reduced-scale display may be implemented by decoding image data stored in the hard disk device 106 and displaying the decoded image on the screen in a reduced scale. When image data has low-resolution icon data for an icon like FlashPix as a standard image format, a reduced-scale image may be displayed using that icon data.

Each icon image can be "selected" using the pointing device 102a. Upon pressing the next candidate button 27, next candidates, i.e., icon images of image data corresponding to $T(8)$ to $T(15)$, are displayed on

the areas 26a to 26h. This operation can be repeated until T(M-1) is reached.

{Description of Step S195}

It is checked in step S195 if the user has
5 selected one of the displayed icon images. If the user has not selected any image, the flow advances to step S197. On the other hand, if the user has selected one icon image, the flow advances to step S196.

{Description of Step S196}

10 In step S196, the icon image selected by the user is copied onto the user drawing area 21. In this case, image data displayed on the display unit 103 may be copied or image data used for displaying a list of image data in step S194 may be used. In this manner, when an
15 icon image close to a desired image appears as a search result, the user need only click that icon image to copy it onto the user drawing area 21, and can modify the contents of the copied image.

Fig. 2 illustrates the user drawing area 21 to
20 have substantially the same size as those of the areas 26a to 26h for displaying icon images. However, the present invention is not limited to such specific layout. For example, the user drawing area 21 may have a relatively larger size to make drawing of an
25 illustration easier, and the areas 26a to 26h may have a smaller size. When the clicked icon image is copied onto

the user drawing area 21, the icon image data to be copied is enlarged to just fall within the user drawing area 21.

The flow then returns to step S192 to make a
5 similar image search using the icon image copied onto the user drawing area 21 as a query criteria.

{Description of Step S197}

It is checked in step S197 if the processing end button 28 has been pressed. If the button 28 has been
10 pressed, the processing ends. On the other hand, if the button 28 has not been pressed, the flow returns to step S191, and the user can continue to draw the illustration.

As described above, according to the first embodiment, the user can select image data stored in the
15 hard disk device 106 instead of drawing an illustration used as a query criteria from the beginning, and can make a similar image search using an image obtained by modifying the selected image. In this manner, upon drawing an illustration, neither drawing skills nor
20 troublesome operations are required, and an efficient similar image search process can be executed.

In the first embodiment, since a similar image search cannot be started unless an illustration is drawn on the user drawing area 21, icon image displayed on the
25 areas 26a to 26h cannot be selected. However, this

shortcoming can be removed by combining another search method.

For example, in an initial state or by user operation, icon images corresponding to image data
5 randomly selected from those stored in the hard disk device 106 may be displayed on the areas 26a to 26h.

On the other hand, the image search method of this embodiment may be combined with a conventional search method that uses attribute information such as a keyword
10 or the like appended to an image as a query criteria. For example, when text "cat" is input, icon images corresponding to image data associated with "cat" are selected from those stored in the hard disk device 106, and are displayed on the areas 26a to 26h. The user
15 selects a desired one of those icon images to copy it onto the user drawing area 21, and can make a similar image search using an image obtained by modifying the copied image as a query criteria. Also, attribute information such as a date of creation, management,
20 correction, or the like of image data may be input as a query criteria.

<Second Embodiment>

In the first embodiment, image data stored in the hard disk device 106 are displayed, a desired one of the
25 displayed images is selected, and an illustration used as a query criteria is drawn on the basis of the

selected image, thus realizing an efficient similar image search process. In the second embodiment, a desired color is selected from the displayed images to change the color used in drawing of an illustration, 5 which is used as a query criteria, on the basis of the selected color, thus realizing an efficient similar image search process.

Since the arrangement and control window of the image search apparatus are the same as those in the 10 first embodiment, a detailed description thereof will be omitted.

An outline of the processes executed by the image search apparatus of the second embodiment will be explained below with reference to Fig. 10.

15 Fig. 10 is a flow chart showing an outline of the processes executed by the image search apparatus of the second embodiment.

Note that the same step numbers denote the same steps as those in the flow chart in Fig. 3 of the first 20 embodiment, and a detailed description thereof will be omitted.

It is checked in step S295 if the user has clicked a point in the displayed icon image where a desired color is present while indicating that point with the 25 cursor 22. If the user has clicked a given point (YES in step S295), the flow advances to step S296 to set the

color at the position of the cursor 22 upon clicking in step S295 to be the color used in drawing. On the other hand, if the user has not clicked any point (NO in step S295), the flow advances to step S297.

5 It is checked in step S297 if search operation is to end. If search operation is not to end (NO in step S297), the flow returns to step S191. On the other hand, if search operation is to end (YES in step S297), the processing ends.

10 With the aforementioned processes, even when icon images themselves displayed as the search results on the areas 26a to 26h are not desired ones, if a portion of the icon image includes a color that the user wants to use in drawing of an illustration, the user moves the
15 cursor 22 to the portion where the color is present, and clicks the mouse, thereby automatically setting that color as that used in drawing. Using the set color, the user can continue to draw the illustration on the user drawing area 21.

20 The details of the processes executed in steps S295 to S297 will be described below.

{Description of Step S295}

 It is checked in step S295 if the user has clicked a point in the displayed icon image list while
25 indicating that point by the cursor 22. If the user has not clicked any point, the flow advances to step S297.

If the user has clicked a given point, the flow advances to step S296.

{Description of Step S296}

In step S296, the color, which is being used in
5 drawing of an illustration, is set at a pixel value at
the clicked position. On the control window, the color
of the cursor 22 is replaced by the set color, thus
informing the user that the color of the cursor 22 has
changed. Also, the color selection scroll bars 23 are
10 changed to indicate the R, G, and B values of the set
color. Normally, the color of the cursor 22 is changed
when the user operates the color selection scroll bars
23. However, in this case, the color selection scroll
bars 23 are used to inform the user of the color set by
15 the aforementioned method. The color set in this step is
used to draw an illustration in step S191.

Note that the pixel value used for setting the
color may be obtained by copying image data displayed on
the display unit 103 or image data corresponding to icon
20 images displayed in a list in step S194. Depending on
the display unit 103, both these image data may be equal
to each other, but in general, the former data is easy
to handle, and the latter data has higher precision. For
example, when image data is compressed by JPEG and is
25 saved in the hard disk device 106, each pixel value is
expressed by 24 bits, but the display unit 103 often

makes a display while lowering the data precision to 8 bits, 15 bits, or 16 bits.

{Description of Step S297}

It is checked in step S297 if the processing end
5 button 28 has been pressed. If the button 28 has been pressed, the processing ends. On the other hand, if the button 28 has not been pressed, the flow returns to step S191, and the user can continue to draw the illustration.

As described above, according to the second
10 embodiment, in order to set or change the color used in drawing of an illustration, the user need only move the cursor 22 to the position of a desired color in an image displayed on the window and click that position in place of making designation (using the color selection scroll
15 bars 23) by means of R, G, and B values, which does not always come as an intuitive method for the user. In this manner, upon drawing an illustration, neither drawing skills nor troublesome operations are required, and an efficient similar image search process can be executed.

20 In the second embodiment, the color used in drawing an illustration is set using icon images displayed as search results. However, another method may be used. For example, if a color can be selected from the illustration on the user drawing area 21, the moving
25 amount of the cursor 22 can be reduced, thus further improving the work efficiency.

In a multi-task OS represented by Windows available from Microsoft Corp., a plurality of applications can be started and can be simultaneously displayed on a single screen. When application software implemented by this embodiment, and another software, e.g., a WWW browser, photo-retouch software, or the like are simultaneously displayed to allow to use a color used in another software, the color selection range can be broadened, and the color used in drawing of an illustration can be selected more efficiently.

On the other hand, when the pointing device 102a having a plurality of buttons including at least first and second buttons is used, a method of setting a color used in drawing an illustration can be selected according to user's purposes. For example, when the user has pressed the first button, the method of setting a color used in drawing an illustration described in the second embodiment is selected; when the user has pressed the second button, a method of setting a color used in drawing an illustration by another software is selected. These methods of setting a color used in drawing an illustration may be selected by forming dedicated buttons on the control window shown in Fig. 2 in place of using the buttons of the pointing device 102a.

The color of the pixel value at the position indicated by the cursor 22, which is controlled by the

pointing device 102a, is used as a color used in drawing
of an illustration. However, since an image normally
contains noise, the color that the user requires does
not always match the pixel value at that point. At this
5 time, when the average value of the pixel values
contained in a small region, e.g., a 3 x 3 (pixel)
square region having the position indicated by the
cursor 22 as the center is used as the color used in
drawing of an illustration, the influences of noise can
10 be suppressed.

In the first and second embodiments, the mouse is
used as the pointing device 102a. However, the present
invention is not limited to such specific pointing
device. For example, when a pen tablet that allows pen
15 input is used, the operator can efficiently draw an
illustration. Also, when a touch screen, which is
integrated with the display unit 103 and allows the user
to directly draw an illustration while observing the
displayed window, is used, more intuitive drawing can be
20 achieved. In addition, any other pointing devices may be
used as long as they can input information to the
computer system.

In step S194, reduced-scale images corresponding
to image data as the processing result of the similar
25 image search process are displayed in a two-dimensional
matrix. However, the reduced-scale images may be lined

up in a horizontal array (one-dimensionally) or may be three-dimensionally displayed in consideration of information in the depth direction. For example, images with higher similarity values may be displayed on the front side (to have larger image sizes), and images with lower similarity values may be displayed on the far side (to have smaller image sizes), thus achieving a list display which is easy to understand at a glance.

<Third Embodiment>

- 10 Upon drawing an illustration used as a query criteria, the illustration drawing method (first drawing method) described in the first embodiment, and that (second drawing method) described in the second embodiment may be selectively executed. For example,
- 15 when the pointing device 102a having a plurality of buttons including at least first and second buttons is used, the drawing method can be selected according to user's purposes. For example, when the user has pressed the first button, the first drawing method is selected;
- 20 when the user has pressed the second button, the second drawing method is selected. In place of using the buttons of the pointing device 102a, the first or second drawing method may be selected by forming dedicated buttons on the control window shown in Fig. 2.

Also, these drawing methods can be combined with the method of setting a color used in drawing of an illustration.

Note that the present invention may be applied to
5 either a system constituted by a plurality of devices (e.g., a host computer, an interface device, a reader, a printer, and the like), or an apparatus consisting of a single equipment (e.g., a copying machine, a facsimile apparatus, or the like).

10 The objects of the present invention are also achieved by supplying a storage medium, which records a program code of a software program that can implement the functions of the above-mentioned embodiments to the system or apparatus, and reading out and executing the
15 program code stored in the storage medium by a computer (or a CPU or MPU) of the system or apparatus.

In this case, the program code itself read out from the storage medium implements the functions of the above-mentioned embodiments, and the storage medium
20 which stores the program code constitutes the present invention.

As the storage medium for supplying the program code, for example, a floppy disk, hard disk, optical disk, magneto-optical disk, CD-ROM, CD-R, magnetic tape,
25 nonvolatile memory card, ROM, and the like may be used.

The functions of the above-mentioned embodiments

may be implemented not only by executing the readout
program code by the computer but also by some or all of
actual processing operations executed by an OS
(operating system) running on the computer on the basis
5 of an instruction of the program code.

Furthermore, the functions of the above-mentioned
embodiments may be implemented by some or all of actual
processing operations executed by a CPU or the like
arranged in a function extension board or a function
10 extension unit, which is inserted in or connected to the
computer, after the program code read out from the
storage medium is written in a memory of the extension
board or unit.

When the present invention is applied to the
15 storage medium, the storage medium stores program codes
corresponding to the flow charts shown in Fig. 3, Fig. 4,
and Figs. 6 to 10.

As many apparently widely different embodiments of
the present invention can be made without departing from
20 the spirit and scope thereof, it is to be understood
that the invention is not limited to the specific
embodiments thereof except as defined in the appended
claims.